## CARMINAWOOD DESIGN

### DOWNSTREAM SANITARY SEWER CAPACITY **ANALYSIS REPORT**

for

**Proposed Apartments** 1130 Orchard Park Road Town of West Seneca, Erie, NY

Prepared for

### Hanley Development

3266 Seneca Street West Seneca, NY 14224

Prepared by

Carmina Wood Design

487 Main Street, Suite 500 Buffalo, NY 14203

Telephone: (716) 842-3165 Fax: (716) 842-0263

May 2022



#### **Project Description**

This project is a development of a 4.90 acre +/- site located on the east side of Orchard Park Road in the Town of West Seneca. The property will be developed to accommodate for 40 2-bedroom apartment units.

The proposed sewer service for this development will connect to an existing 10" Town of West Seneca sewer main the runs along the east side of Orchard Park Road.

#### Node 1 - 1001 Orchard Park Rd (12"):

Existing Peak Flow measured (wet weather event) = 3.049 cfs (1.969 mgd)\*

Proposed Apartments Peak Flow = 0.041 cfs\*\*
Proposed Total Peak Flow = 3.090 cfs

Existing Peak Flow measured (overall) = 3.249 cfs (2.100 mgd)\*

Proposed Apartments Peak Flow = 0.041 cfs\*\*
Proposed Total Peak Flow = 3.290 cfs

Theoretical capacity of existing 12" pipe @ 0.34% = 2.249 cfs

<u>Conclusion:</u> Monitored flows the day following the 0.51" rainfall event exceeded the capacity of the existing pipe 12" sewer. One time during the monitoring period the flow depth exceeded the pipe diameter at Node 1, but at no time during the monitoring period did the flow at any point slow or stall which would have caused a backup or flooding at the manhole. I/I mitigation shall be required for the contribution proposed for this project.

### Node 2 - Orchard Park Rd (15"):

Existing Peak Flow measured (wet weather event) = 1.908 cfs (1.233 mgd)\*

Proposed Apartments Peak Flow = 0.041 cfs\*\*
Proposed Total Peak Flow = 1.949 cfs

Existing Peak Flow measured (overall) = 2.584 cfs (1.670 mgd)\*

Proposed Apartments Peak Flow = 0.041 cfs\*\*
Proposed Total Peak Flow = 2.625 cfs

Theoretical capacity of existing 15" pipe @ 0.34% = 4.077 cfs

<u>Conclusion:</u> Monitored flows the day following the 0.51" and 0.21" rainfall events exceeded the capacity of the existing pipe 12" sewer. Three times during the monitoring period the flow depth exceeded the pipe diameter at Node 1, but at no time during the monitoring period did the flow at any point slow or stall which would have caused a backup or flooding at the manhole. I/I mitigation shall be required for the contribution proposed for this project

#### Node 3 - Orchard Park Rd & Fairfax (48"):

Existing Peak Flow measured (wet weather event) = 14.470 cfs (9.352 mgd)\*

Proposed Apartments Peak Flow = 0.041 cfs\*\*
Proposed Total Peak Flow = 14.511 cfs

Existing Peak Flow measured (overall) = 16.150 cfs (10.438 mgd)\*

Proposed Apartments Peak Flow = 0.041 cfs\*\*
Proposed Total Peak Flow = 16.191 cfs

Theoretical capacity of existing 48" pipe @ 0.15% = 60.218 cfs


<u>Conclusion:</u> The proposed total peak flow is less than the capacity of the 48" pipe, therefore there is sufficient capacity. At no time during the monitoring period did flow depth exceed the pipe diameter at Node 3 of the downstream monitoring points during the rain events monitored.

### Foot Notes:

Downstream capacity node information provided by Town of West Seneca \*Converted from measurements in TECSmith report dated 4/19/22 \*\* See Sanitary Sewage Demand Calculations

### **Location Map**

# ArcGIS Web Map



© OpenStreetMap (and) contributors, CC-BY-SA

## **Sanitary Demand Calculations**

### CARMINA WOOD DESIGN

487 MAIN STREET, SUITE 500 BUFFALO, NEW YORK, 14203 (716) 842-3165

FAX (716) 842-0263

Project No.:

22.128

Date:

5/9/2022

Project Name:

Residential Apartments

Subject:

Project Address: 1130 Orchard Park Road West Seneca, NY Sanitary Sewer Demand Calcs

Sheet:

1 of 1

Proposed Towhouses								
220 gal/d/unit	x 28 units	=	6,160	gpd		*use 220 gal	lons per unit p	per day (2-bdrm
			-5 o-m o b -mo					
Total Site Sanitary Demand:		= '	<u>6,160</u>	<u>gpd</u>				
d Peak Sanitary Demand:								
Peaking Factor based on Popula	ation:							
		100	gpcd	= 62	2 per c	apita		
	Population (P)			62 people	e			
Peaking Factor: (18 +Öl	P) / (4 + ÖP )	wł	nere P is in	thousands				
				ame governe e				
Peaking Factor =	4.30							
Peak Sanitary Demand =	6,160 x	4.30		26,460 gp 0.026 MC				
				0.026 MC				
			_	0.041 (13	5			
				0.041 CIS				
uired Infiltration and Inflow Mitig	ation:			U.U41 CIS				
	ation:		26 460			18 38 gpm		
Peak Sanitary Flow			26,460	gpd =	1	8.38 gpm		
					1	18.38 gpm 73.50 gpm req'	d	
Peak Sanitary Flow			18.38	gpd =	1		d	
Peak Sanitary Flow 4:1 offset flow per NYSDEC require			18.38	gpd = x 4 =	1		d	
Peak Sanitary Flow 4:1 offset flow per NYSDEC require Mitigation Credit			18.38 30	gpd = x 4 = gpm / late	1 7 eral	73.50 gpm req		ed by the Town
Peak Sanitary Flow 4:1 offset flow per NYSDEC require Mitigation Credit			18.38 30 2.5	gpd = x 4 = gpm / late	1 7 eral	73.50 gpm req		ed by the Town
Peak Sanitary Flow 4:1 offset flow per NYSDEC require Mitigation Credit			18.38 30 2.5	gpd = x 4 = gpm / late	1 7 eral	73.50 gpm req		ed by the Town
Peak Sanitary Flow 4:1 offset flow per NYSDEC require Mitigation Credit			18.38 30 2.5	gpd = x 4 = gpm / late	1 7 eral	73.50 gpm req		
Peak Sanitary Flow 4:1 offset flow per NYSDEC require Mitigation Credit			18.38 30 2.5	gpd = x 4 = gpm / late	1 7 eral	73.50 gpm req		
Peak Sanitary Flow 4:1 offset flow per NYSDEC require Mitigation Credit			18.38 30 2.5	gpd = x 4 = gpm / late	1 7 eral	73.50 gpm req		
Peak Sanitary Flow 4:1 offset flow per NYSDEC require Mitigation Credit			18.38 30 2.5	gpd = x 4 = gpm / late	1 7 eral	73.50 gpm req		
Peak Sanitary Flow 4:1 offset flow per NYSDEC require Mitigation Credit			18.38 30 2.5	gpd = x 4 = gpm / late	1 7 eral	73.50 gpm req		
Peak Sanitary Flow 4:1 offset flow per NYSDEC require Mitigation Credit			18.38 30 2.5	gpd = x 4 = gpm / late	1 7 eral	73.50 gpm req		

# **TECSmith Monitoring Report**

1001 Orchard Park Rd (12")	Node 1 Orchard Park Rd (12")	d (42")		Orcha	Node 2	" (45")		Node 3	mor, s	Rain	Snow
AK	AK	AK	EI OW DEA	DE L	K ELOW	=	Orchard	Orchard Park Kd & Fairtax (48")	rtax (48")		
00) (MGD) LEVEL (IN) (GAL x 1,000)	(MGD) LEVEL (IN) (GAL x 1,000)	(GAL x 1,000)		i L	(MDG)	LEVEL (IN)	(GAL x 1,000)	PEAK FLOW (MDG)	PEAK LEVEL (IN)	(inches)	(inches)
0.451 6.624 341.293	6.624 341.293	341.293			0.804	5.176	3196.614	6.783	13.938	0	0
0.429 6.354 435.456	6.354 435.456	435.456			0.771	4.387	5684.090	6.485	13.639	0	0
0.634 7.566 437.597	7.566 437.597	437.597			0.903	4.881	6314.024	7.874	17.857	0.27	0
0.774 8.054 595.846	8.054 595.846	595.846			0.958	14.897	7506.892	9.168	20.985	0.08	0
0.601	6.762		540.386		0.766	5.802	6601.632	8.220	19.365	0	0
0.435	6.572	Ì	484.695		0.730	4.786	5911.885	6.708	14.066	0	0
1.969	50.259		526.604		1.233	39.448	6366.253	9.352	21.857	0.51	0
2.100 56.546	56.546	+	885.440		1.670	56.717	8410.107	10.438	23.577	0	0
0.536 6.827 496.776	6.827 496.776	496.776			0.699	4.932	7059.230	8.020	19.386	0	0
0.627 7.108 516.156	7.108 516.156	08 516.156			0.795	5.453	7112.401	8.489	19.148	0.09	0.1
0.734 7.121 502.699	7.121 502.699	502.699			0.753	5.041	7001.414	8.461	18.753	90.0	2.3
0.527 6.418 442.380	6.418 442.380	442.380			0.695	4.585	6396.917	7.538	17.111	0.01	0.4
0.686 6.476 415.768	6.476 415.768	415.768			0.633	4.392	5909.058	6.957	14.053	0	0
0.779 8.492 433.907	8.492 433.907	433.907			.012	6.066	5521.696	6.653	13.811	0.01	0
0.721 7.500 494.235	7.500 494.235	494.235			0.758	5.331	5943.213	7.661	16.548	0.09	0
0.831 6.688 435.101	6.688 435.101	435.101			0.713	4.533	5419.635	6.277	14.053	90.0	0.1
6.353 405.887	6.353 405.887	405.887		0	0.651	4.547	5147.186	6.140	13.371	0	0
0.505 6.247 359.789	6.247 359.789	359.789			0.669	4.488	5083.174	6.186	13.093	0.01	0
297.479 0.640 6.107 372.366	6.107 372.366	372.366			0.579	4.773	4946.766	6.325	12.723	0	0
283.690 0.458 6.281 375.176	6.281 375.176	375.176			0.581	4.631	4901.882	5.708	12.382	0	0
0.506 6.715 370.221	6.715 370.221	370.221	4		0.577	4.801	4842.495	5.943	12.848	0.21	0
1.149 9.528 735.759	9.528 735.759	735.759		Ì	1.262	22.143	7751.294	9.369	21.493	0.25	0
0.605 6.946 610.050	6.946 610.050	610.050			0.853	5.537	7000.725	8.355	18.804	0	0
0.445 6.583 476.833	6.583 476.833	476.833			0.727	5.010	6041.826	7.017	13.864	0	0
0.621 6.165 398.460	6.165 398.460	398.460			0.659	4.727	5473.970	6.521	13.216	0	0
0.553 7.058 403.992	7.058 403.992	403.992			0.672	5.088	5257.193	7.976	15.138	0.13	0
601.005	7.835 601.005	601.005		)	0.858	5.988	7299.038	9.109	16.993	0.14	0
0.486 6.814 514.574	6.814 514.574	514.574			0.827	4.977	6134.522	7.267	14.479	0.05	0
202.051 0.422 6.249 298.422	6.249		298.422		0.686	4.750	3692.282	6.917	14.240	0	0
		-	1			1	-		1	1.97	2.9
MGD CFS		CES	L		MGD	CES	_	MGD	CFS		
0.5	0.5				2	;		1	ָּהָ ק		

Wet         1.969         3.046         Wet         1.233         1.908         Wet         9.352         14.47           Dry         2.100         3.249         Dry         1.670         2.584         Dry         10.438         16.15		MGD	CFS		MGD	CFS		GDIM	CFS
2.100 3.249 <b>Dry</b> 1.670 2.584 <b>Dry</b> 10.438	Wet	1.969	3.046	Wet	1.233	1.908	Wet	9.352	14.470
	Dry	2.100	3.249	Dry	1.670	2.584	Dry	10.438	16.150

# **TECsmith**

TECSMITH, Inc. PO Box 383 Elma, New York 14059-0383 Tel: 716-462-0382 Fax: 716-687-1418

Date: April 19, 2022

### SANITARY SEWER FLOW CAPACITY STUDY - Summary Review

Prepared For: 1130 Orchard Park Road Capacity Analysis

R. Christopher Wood, PE Partner 487 Main Street, Suite 500 Buffalo, New York 14203

Project Name: 1130 Orchard Park Road Capacity Analysis

Flow Monitoring Period: March 17, 22 to April 14, 2022

Rain Events (> 0.5-inches) Monitored: March 23, (0.51")

Number of Monitoring Nodes: Three (3) downstream manholes

### **Node Locations and Descriptions:**

Node 1

1001 Orchard Park Rd (12")

Node 2

Orchard Park Rd (15")

Node 3

Orchard Park Rd & Fairfax (48")

### **Summary Conclusion:**

Based on the data presented in this report, specifically the flow depth measurements recorded (see graphs below)


- One time the flow depth exceeds pipe diameter at Node 1 of the downstream monitoring points during the wet weather events monitored.
- Two times the flow depth exceeds pipe diameter at Node 2 of the downstream monitoring points during the wet weather events monitored.
- At no time the flow depth exceeds pipe diameter at Node 3 of the downstream monitoring points during the wet weather events monitored.

TECSMITH, Inc. PO Box 383 Elma, New York 14059-0383 Tel: 716-462-0382 Fax: 716-687-1418

### **Depth of Flow Capacity Summary:**


Depth of flow capacity is based on diameter of pipe. See graphs below.

• One time during the monitoring period did depth of flow exceed pipe diameter at Node 1.




TECSMITH, Inc. PO Box 383 Elma, New York 14059-0383 Tel: 716-462-0382 Fax: 716-687-1418

• Two times during the monitoring period did depth of flow exceed pipe diameter at Node 2.



TECSMITH, Inc. PO Box 383 Elma, New York 14059-0383 Tel: 716-462-0382 Fax: 716-687-1418

• At no time during the monitoring period did depth of flow exceed pipe diameter at Node 3.



Sewer Node Maps

